

batchONE GO

Ready, Set, Go

Quality Automation for Home Growers

| Trim Type | Feed (lbs/hr) | Feed (kg/hr) |
|-----------|---------------|--------------|
| Dry | Up to 5 | Up to 2.3 |



WATCH IT IN ACTION

TWISTERTRIMMER.COM/BATCHONE-GO



Quality Automation

Engineered to make dry trimming your small batch a breeze. Made of aircraft grade aluminum and electropolished food grade stainless steel. With quality, affordability and a throughput of 5 lbs/hr there is nothing on the market that even comes close.

58dB

Whisper Quiet

You would be kicked out of a library for laughing before you would for trimming with the BatchOne Go. Rated at 58 decibels, feel free to trim during your next video call or even at the crack of dawn.



30 Second Setup

With only 6 removable pieces and a smooth edgeless internal wall design, the BatchOne Go combines the industry's most gentle trimming process, frictionless trim capture into one portable, easy to clean package.

BatchOne Go Features

- Optically Clear Magnetic Lid
- Easy-lock Tumbler Lid
- Frictionless Trim Capture
- Unique frame design allows for simple loading and unloading
- Quiet 58 decibels operation
- Fine saddle tension adjustments for tight trimming
- Anti-stall powerful 40W motor
- Lubrication free, mess-free operation
- Capture 100% of the trim without the need of a vacuum or Trim Saver
- Anti-slip durable rubber feet for grip while operating and cleaning
- Easy to remove motor assembly allows for fast machine cleaning with a pressure washer without damage to sensitive electronics
- Quick tumbler removal without removing fasteners
- Non-coated, electropolished 304 stainless steel tumbler
- FDA compliant materials
- CSA, UL, CE Certified




TWISTER

batchONE GO



NORTH AMERICAN MODEL

EUROPEAN MODEL

| | | |
|-----------------------|---|-----------------------|
| SPECIFICATIONS | Product Number | 02-10085A |
| | Input Voltage | 120V, 60 Hz |
| | Current Draw | 0.5A |
| | Circuit Breaker | 15A |
| | Tumbler Motor | 40W |
| | Tumbler Speed | 23RPM |
| | Tumbler Diameter | 10in / 25.4cm |
| | Tumbler Slots | 0.188in / 0.48cm |
| | Sound Rating | 58dB |
| | Length | 22.4in / 56.9cm |
| | Width | 13.9in / 35.3cm |
| | Height | 19.6in / 50cm |
| | Weight | 48lbs / 22kg |
| | Weight (without motor assembly) | 34lbs / 16.3kg |
| | Shipping Weight | 55lbs / 25kg |
| | Power Inlet | IEC C14 |
| | Power Cable | IEC C13 to NEMA 5-15P |
| Certifications |  | |

| | | |
|-----------------------|---------------------------------|--------------------|
| SPECIFICATIONS | Product Number | 02-10086A |
| | Input Voltage | 240V, 50 Hz |
| | Current Draw | 0.4A |
| | Circuit Breaker | 10A |
| | Tumbler Motor | 40W |
| | Tumbler Speed | 24RPM |
| | Tumbler Diameter | 10in / 25.4cm |
| | Tumbler Slots | 0.188in / 0.48cm |
| | Sound Rating | 58dB |
| | Length | 22.4in / 56.9cm |
| | Width | 13.9in / 35.3cm |
| | Height | 19.6in / 50cm |
| | Weight | 48lbs / 22kg |
| | Weight (without motor assembly) | 34lbs / 16.3kg |
| | Shipping Weight | 55lbs / 25kg |
| | Power Inlet | IEC C14 |
| | Power Cable | IEC C13 to CEE 7/7 |
| Certifications | CE RoHS | |

Visit twistertrimmer.com or call your Twister Rep for an extensive list of replacement parts or accessories.

